




FR Protection

Intended to be worn over primary FR apparel to protect it from grease, dirt and non-toxic liquids, in order to extend the life of the primary FR.


Passes ASTM D6413 vertical flame resistance test. Breathable fabric chars – no flame or molten drip. Recommended applications include turnarounds, oil & gas, manufacturing, and industrial.

Available Garments




Coverall with Elastic Wrists and Open Ankles

#9012
Size: Medium- 5XL
25 per case



Coverall with Attached Hood, Elastic Wrists and Ankles

#9015
Size: Medium- 5XL
25 per case



Coverall with Attached Hood and Boots, Elastic Wrists

#9019
Size: Medium- 5XL
25 per case

PyroGuard FR®

TEST CONDUCTED	TEST METHOD	RESULTS
Grab / Tensile - Machine Direction	ASTM D5034-2001	34 lbs.
Grab / Tensile- Cross Direction	ASTM D5034-2001	26 lbs.
Vertical Flammability - Machine Direction	ASTM D6413	Pass
Vertical Flammability - Cross Direction	ASTM D6413	Pass
Electrostatic Decay Rate	ASTM D257	Pass



- Phosphate-based fire retardant deprives flames of their fuel source
- High moisture vapor transmission rate (MVTR) helps wearers feel cooler
- Elastic back stretches with user for more comfort and better tear resistance
- Storm flap over zipper adds an extra layer of protection
- Passes ASTM D6413 Vertical Flame Testing
- Meets NFPA 2113 requirement for section 5.1.9